

| NETWORK ÜRÜNLER                                          |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| ÜRÜN KODU<br>(Model Number)                              | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                        | Liste<br>(MSRP) |
| 2MP IP KAMERA                                            |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |
| <b>YENİ</b><br>DS-2CD1021G2-LIUF<br>(Dahili mikrofon)    |                                                                                           | <b>2 MP Smart Hybrid Light Bullet Network Kamera</b><br>1/2.9" Progressive Scan CMOS, ICR,<br>1920x1080:25fps(P)/30fps(N),<br>H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m,<br>DC12V & PoE,Support mobile monitoring via Hik-Connect , TF<br>card slot, *power supply no included. Motion Detection 2.0                                                                                                                          | 84              |
| <b>YENİ</b><br>DS-2CD1121G2-LIUF<br>(Dahili mikrofon)    |                                                                                           | <b>2 MP Smart Hybrid Light Dome Network Kamera</b><br>1/2.9" Progressive Scan CMOS, ICR,<br>1920x1080:25fps(P)/30fps(N),<br>H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m,<br>DC12V & PoE,Support mobile monitoring via Hik-Connect , TF<br>card slot, *power supply no included. Motion Detection 2.0                                                                                                                            | 84              |
| DS-2CD1023G2-LIUF<br>(Dahili mikrofon)                   |                                                                                           | <b>2 MP Smart Hybrid Light Bullet Network Kamera</b><br>High quality imaging with 2 MP resolution; Support Human and<br>Vehicle Detection; Smart Hybrid Light: advanced technology with<br>long range; Built-in microphone for real-time audio security;<br>Efficient H.265+ compression technology; Support on-board<br>storage up to 512 GB (SD card slot); Water and dust resistant<br>(IP67);Motion Detection 2.0                     | 91              |
| DS-2CD1323G2-LIUF<br>(Dahili mikrofon)                   |                                                                                         | <b>2 MP Smart Hybrid Light Turret Network Kamera</b><br>High quality imaging with 2 MP resolution; Support Human and<br>Vehicle Detection; Smart Hybrid Light: advanced technology with<br>long range; Built-in microphone for real-time audio security;<br>Efficient H.265+ compression technology; Support on-board<br>storage up to 512 GB (SD card slot) (Optional); Water and dust<br>resistant (IP67);                              | 91              |
| DS-2CD1023G2-LIUF/M<br>(Dahili mikrofon)                 |                                                                                         | <b>2 MP Smart Hybrid Light Bullet Network Kamera<br/>Full Metal</b><br>High quality imaging with 2 MP resolution; Support Human and<br>Vehicle Detection; Smart Hybrid Light: advanced technology with<br>long range; Built-in microphone for real-time audio security;<br>Efficient H.265+ compression technology; Support on-board<br>storage up to 512 GB (SD card slot); Water and dust resistant<br>(IP67);Motion Detection 2.0      | 99              |
| <b>YENİ</b><br>DS-2CD1T23G2-LIUF/SL<br>(Dahili mikrofon) | <br> | <b>2 MP Smart Hybrid Light Bullet Network Kamera<br/>Live Guard</b><br>1/3" Progressive CMOS, ICR,1920 × 1080: 25fps(P)/30fps(N),<br>H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white<br>light range: <b>up to 50m</b> , Built-in microphone & speaker, audio &<br>strobe light alarm, DC12V & PoE, Support mobile monitoring via<br>Hik-Connect; Support on-board storage up to 512 GB (SD card<br>slot) - Motion Detection 2.0 | 131             |

| ÜRÜN KODU<br>(Model Number)                               | RESİM<br>(Picture)                                                                              | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-2CD1027G2H-LIUF<br>(Dahili mikrofon)                   | <br>ColorVu    | 2 MP ColorVu & Smart Hybrid Light Bullet Network Kamera<br>High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0                                            | 117             |
| DS-2CD1327G2H-LIUF<br>(Dahili mikrofon)                   | <br>ColorVu    | 2 MP ColorVu & Smart Hybrid Light Dome Network Kamera<br>High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0                                              | 117             |
| <b>YENİ</b><br>DS-2CD1T27G2H-LIUF/SL<br>(Dahili mikrofon) | <br>ColorVu    | <b>2 MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera Live Guard</b><br>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included; Motion Detection 2.0                                                                      | 150             |
| DS-2CD1623G2-LIZSU<br>(Dahili mikrofon)                   |              | <b>2MP Motorize Varifokal Lensli IR Bullet Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b><br>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio<br>*power supply is not included                                                         | 190             |
| DS-2CD1723G2-LIZSU<br>(Dahili mikrofon)                   |              | <b>2MP Motorize Varifokal Lensli IR Dome Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b><br>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio<br>*power supply is not included                                                           | 190             |
| DS-2CD2523G2-LIS2U<br>(Dahili mikrofon)                   | <br>AcuSense | <b>2MP IR Mini Dome Acusense Kamera Acusense &amp; Smart Hybrid Light &amp; 120dB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO<br>* -2U: Built-in Dual-Array Microphone | 239             |

| ÜRÜN KODU<br>(Model Number)                                                                                                       | RESİM<br>(Picture)                                                                                                                                                     | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                           | Liste<br>(MSRP) |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br>DS-2CD2T23G2-LIS2U/SL<br><br> | <br> | <b>2MP Bullet Acusense Kamera &amp; Live Guard &amp; Acusense &amp; Smart Hybrid Light &amp; 120dB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR;<br>BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot;<br>HIK-Connect cloud service<br>*-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m<br>*-2U:Built-in Dual-Array Microphone; | <b>236</b>      |
| <b>4MP IP KAMERA</b>                                                                                                              |                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                 |
| <b>YENİ</b><br><br>DS-2CD1041G2-LIUF<br>(Dahili mikrofon)                                                                         |                                                                                       | <b>4 MP Smart Hybrid Light Fixed Bullet Network Kamera</b><br>1/2.8" Progressive Scan CMOS, ICR, 2560 × 1440:25fps(P)/30fps(N),<br>H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m,<br>DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0                                                                                                                                                                            | <b>117</b>      |
| <b>YENİ</b><br><br>DS-2CD1141G2-LIUF<br>(Dahili mikrofon)                                                                         |                                                                                       | <b>4 MP Smart Hybrid Light Fixed Dome Network Kamera</b><br>1/2.8" Progressive Scan CMOS, ICR, 2560 × 1440:25fps(P)/30fps(N),<br>H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m,<br>DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0                                                                                                                                                                              | <b>117</b>      |
| DS-2CD1043G2-LIUF<br>(Dahili mikrofon)                                                                                            |                                                                                     | <b>4MP Smart Hybrid Light Bullet Network Kamera</b><br>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0                                                                             | <b>128</b>      |
| DS-2CD1343G2-LIUF<br>(Dahili mikrofon)                                                                                            |                                                                                     | <b>4MP Smart Hybrid Light Turret Network Kamera</b><br>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0                                                                             | <b>128</b>      |
| DS-2CD1043G2-LIUF/M<br>(Dahili mikrofon)                                                                                          |                                                                                     | <b>4MP Smart Hybrid Light Bullet nETWORK Kamera Full Metal</b><br>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0                                                                  | <b>135</b>      |

| ÜRÜN KODU<br>(Model Number)                       | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                 | Liste<br>(MSRP) |
|---------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                       |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                 |
| <b>DS-2CD1T43G2-LIUF/SL</b><br>(Dahili mikrofon)  |    | <b>4MP Smart Hybrid Light Bullet Network Kamera</b><br><b>Live guard</b><br>1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, Smart Hybrid Light with IR and white light, range: up to 50m, DC12V & PoE, Motion 2.0 human and vehicle classification, Support mobile monitoring via Hik-Connect; *power supply not included<br>*-F: Built-in Microphone, TF card slot; Motion Detection 2.0 | <b>168</b>      |
| <b>DS-2CD1047G2H-LIUF</b><br>(Dahili mikrofon)    |    | <b>4MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera</b><br>1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included; Motion Detection 2.0                                                                               | <b>157</b>      |
| <b>DS-2CD1347G2H-LIUF</b><br>(Dahili mikrofon)    |    | <b>4MP ColorVu &amp; Smart Hybrid Light Turret Network Kamera</b><br>1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included; Motion Detection 2.0                                                                               | <b>157</b>      |
| <b>YENİ</b>                                       |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                 |
| <b>DS-2CD1T47G2H-LIUF/SL</b><br>(Dahili mikrofon) |  | <b>4MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera</b><br>1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; <b>IR and white light, up to 50m</b> *-F: SD Card Slot (up to 512GB)<br>*power supply is not included; Motion Detection 2.0                                             | <b>212</b>      |
| <b>DS-2CD1643G2-LIZSU</b><br>(Dahili mikrofon)    |  | <b>4MP Smart Hybrid Light Motorize Varifokal Lensli Bullet Kamera 120dB WDR</b><br>1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect; *-S: alarm and audio; *power supply is not included<br>; Motion Detection 2.0                                                  | <b>219</b>      |
| <b>DS-2CD1743G2-LIZSU</b><br>(Dahili mikrofon)    |  | <b>4MP Smart Hybrid Light Motorize Varifokal Lensli Dome Kamera 120dB WDR</b><br>1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect; *-S: alarm and audio; *power supply is not included                                                                              | <b>219</b>      |

| ÜRÜN KODU<br>(Model Number)                      | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Liste<br>(MSRP) |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-2CD2043G2-LI2U<br>(Dahili mikrofon)           |                                                                                           | <b>4M Smart Hybrit Light Bullet Network Kamera</b><br><b>Acusens &amp; Full-Metal &amp; VCA &amp; 120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2U:Built-in Dual-Array Microphone                             | 228             |
| DS-2CD2143G2-LIS2U<br>(Dahili mikrofon)          |                                                                                           | <b>4M Smart Hybrit Light Dome Network Kamera</b><br><b>Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO<br>* -2U:Built-in Dual-Array Microphone | 239             |
| DS-2CD2543G2-LIS2U<br>(Dahili mikrofon)          |                                                                                          | <b>4M Smart Hybrit Light Dome Network Kamera</b><br><b>Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO<br>* -2U:Built-in Dual-Array Microphone | 262             |
| <b>YENİ</b>                                      |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                 |
| DS-2CD2T43G2-LIS2U/SL<br>(Dahili mikrofon)       | <br> | <b>4M Smart Hybrit Light Bullet Network Kamera</b><br><b>Acusens &amp; Full Meal &amp; VCA &amp; 120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service<br>*-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m<br>* -2U:Built-in Dual-Array Microphone       | 251             |
| <b>YENİ</b>                                      |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                 |
| DS-2CD2046G2H-I2U/SL<br>(Powered by Darkfighter) | <br> | <b>4M Darkfight Bullet Network Kamera</b><br><b>Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with light;<br>25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone; -/SL: live-guard                   | 266             |

| ÜRÜN KODU<br>(Model Number)                                                                                                                           | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-2CD2146G2H-ISU<br>(Powered by Darkfighter)                                                                                                         |                                                                                           | <b>4M Darkfight Dome Network Kamera</b><br><b>Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA<br>functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect<br>cloud service; -U:Built-in microphone                                                | 266             |
| <b>YENİ</b><br>DS-2CD2T46G2H-IS2U/SL<br>(Powered by Darkfighter)<br> | <br>     | <b>4M Darkfight Bullet Network Kamera</b><br><b>Live Gaurd Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA<br>functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE;<br>Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance               | 296             |
| <b>YENİ</b><br>DS-2CD2047G3-LI2UY/SL<br>(Darkfighter)<br>          | <br>   | <b>4M ColorVu + Smart Hybrid Bullet Network Kamera</b><br><b>Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light<br>25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA<br>functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR,<br>up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-<br>Connect cloud service; -U:Built-in microphone    | 357             |
| <b>YENİ</b><br>DS-2CD2347G3-LIS2UY/SL<br>(Darkfighter)<br>         | <br> | <b>4M ColorVu + Smart Hybrid Turret Network Kamera</b><br><b>Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light<br>25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA<br>functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR,<br>up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-<br>Connect cloud service;<br>-U:Built-in microphone | 357             |
| <b>YENİ</b><br>DS-2CD2T47G3-LIS2UY/SL<br>(Darkfighter)<br>         | <br> | <b>4M ColorVu + Smart Hybrid Bullet Network Kamera</b><br><b>Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light<br>25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA<br>functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR,<br>up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-<br>Connect cloud service;                           | 418             |

| ÜRÜN KODU<br>(Model Number)                                                                                                                                  | RESİM<br>(Picture)                                                                                                                                                             | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Liste<br>(MSRP) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>DS-2CD2643G2-LIZS2U</b><br>(Dahili mikrofon)<br><br>                     |                                                                                               | <b>4MP Motorize Varifokal Lensli Smart Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 60m;<br>Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot;<br>HIK-Connect cloud service;<br>Audio/Alarm IO; Built-in Dual-Array Microphone | 399             |
| <b>DS-2CD2743G2-LIZS2U</b><br>(Dahili mikrofon)<br><br>                     |                                                                                               | <b>4MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;<br>25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams;<br>3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service<br>*-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m<br>*-2U:Built-in Dual-Array Microphone                   | 399             |
| <b>DS-2CD2646G2HT-IZS(2.8-12mm)</b><br>(Powered by Darkfighter)<br><br>   |                                                                                              | <b>4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR</b><br>1/3" Progressive Scan CMOS((C) model);<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Powered by Darkfighter technology,Color: 0.003 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520,1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm I/O<br>*non-(C) model:1/2.7" Progressive Scan CMOS                 | 475             |
| <b>DS-2CD2746G2H-IPTRZS(2.8-12mm)</b><br>(Powered by Darkfighter)<br><br> |                                                                                             | <b>4MP PTRZ Motorize Varifokal Lensli IR Dome Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; PTRZ</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m;<br>DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;                                                                       | 475             |
| <b>DS-2CD2647G3-LIZS2UY/SL</b><br>(Darkfighter)<br><br>                   | <br><br> | <b>4MP Colorvu Motorize Varifokal Lensli Hybrid Light Bullet Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008Lux @ (F1.2, AGC ON),0 Lux with light<br>25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>/:SL Live Guard                                         | 657             |

| ÜRÜN KODU<br>(Model Number)                                                          | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                    | Liste<br>(MSRP) |
|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br>DS-2CD2747G3T-LIZSY(2.8-12mm)<br>(Darkfighter)<br><br>ColorVu 3.0 |                                                                                           | <b>4MP Motorize Varifokal Lensli Smart Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA 120dB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light<br>25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service; | <b>657</b>      |
| <b>6MP IP KAMERA</b>                                                                 |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| DS-2CD1063G2-LIUF<br>(Dahili mikrofon)                                               |                                                                                           | <b>6MP Mini IR Bullet Kamera Smart Hybrid Light</b><br>High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional); Motion detection 2.0                                                                                       | <b>164</b>      |
| DS-2CD1363G2-LIUF<br>(Dahili mikrofon)                                               |                                                                                           | <b>6MP Turret Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b><br>High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional);                                                                                         | <b>164</b>      |
| <b>YENİ</b><br><br>DS-2CD1T63G2-LIUF/SL<br>(Dahili mikrofon)                         | <br> | <b>6MP Bullet Kamera Smart Hybrid Light &amp; Motion Detection 2.0 &amp; Live Guard</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*power supply is not included                                                                  | <b>186</b>      |
| DS-2CD1067G2H-LIUF<br>(Dahili mikrofon)<br><br>ColorVu                               |                                                                                         | <b>6MP Mini Bullet Kamera (H.265+) ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included                                                          | <b>183</b>      |
| DS-2CD1367G2H-LIUF<br>(Dahili mikrofon)<br><br>ColorVu                               |                                                                                         | <b>6MP Mini Bullet Kamera ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included                                                                   | <b>183</b>      |

| ÜRÜN KODU<br>(Model Number)                       | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Liste<br>(MSRP) |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                       |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                 |
| <b>DS-2CD1T67G2H-LIUF/SL</b><br>(Dahili mikrofon) | <br>     | <b>6MP Mini Bullet Kamera (H.265+) ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0 &amp; Live Guard</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; 50 m IR<br>*-F: SD Card Slot (up to 512GB)<br>*power supply is not included<br>/SL: live Guard                                                                               | <b>230</b>      |
| <b>DS-2CD1663G2-LIZSU</b><br>(Dahili mikrofon)    |                                                                                           | <b>6MP Smart Hybrit Light Motorize Varifokal Lensli Bullet Kamera (H.265+) 120dB WDR</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect<br>*-S: alarm and audio<br>*power supply is not included                                                                                                                     | <b>230</b>      |
| <b>DS-2CD1763G2-LIZSU</b><br>(Dahili mikrofon)    |                                                                                          | <b>6MP Smart Hybrit Light Motorize Varifokal Lensli Dome Kamera (H.265+) 120dB WDR</b><br>1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect<br>*-S: alarm and audio<br>*power supply is not included                                                                                                                       | <b>230</b>      |
| <b>8MP IP KAMERA</b>                              |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                 |
| <b>DS-2CD2083G2-LI2U</b><br>(Dahili mikrofon)     | <br> | <b>8M Smart Hybrit Light Mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>* -2U: Built-in Dual-Array Microphone                       | <b>285</b>      |
| <b>DS-2CD2183G2-LIS2U</b><br>(Dahili mikrofon)    | <br> | <b>8M Smart Hybrit Light Dome Camera Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*-S model: Audio/Alarm IO<br>* -2U: Built-in Dual-Array Microphone | <b>296</b>      |

| ÜRÜN KODU<br>(Model Number)                                                                                                                                    | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Liste<br>(MSRP) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>DS-2CD2583G2-LI2U</b><br>(Dahili mikrofon)<br><br>                         |                                                                                           | <b>8M Smart Hybrit Light Mini Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*-S model: Audio/Alarm IO<br>*-2U:Built-in Dual-Array Microphone                | 323             |
| <b>YENİ</b><br><br><b>DS-2CD2T83G2-LIS2U/SL</b><br>( Dahili mikrofon)<br><br> | <br>     | <b>8M Smart Hybrit Light Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; live guard</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m<br>*-2U:Built-in Dual-Array Microphone | 323             |
| <b>YENİ</b><br><br><b>DS-2CD2086G2H-I2U/SL</b><br>( Darkfighter)<br><br>    | <br> | <b>8M Darkfight mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>-U:Built-in micphone                                        | 342             |
| <b>DS-2CD2186G2H-ISU</b><br>(Darkfighter)<br><br>                           |                                                                                         | <b>8M Darkfight Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>-U:Built-in micphone                                                                | 357             |
| <b>YENİ</b><br><br><b>DS-2CD2T86G2H-IS2U/SL</b><br>( Darkfighter)<br><br>   | <br> | <b>8M Darkfight Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;<br>25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance                     | 429             |

| ÜRÜN KODU<br>(Model Number)                                                                                                                                         | RESİM<br>(Picture)                                                                                                                                                             | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br><b>DS-2CD2087G3-LI2UY/SL</b><br><b>(Darkfighter)</b><br><br>    | <br><br>     | <b>8M ColorVu+ Hybrid mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>-U: Built-in microphone               | <b>418</b>      |
| <b>YENİ</b><br><br><b>DS-2CD2387G3-LIS2UY/SL</b><br><b>(Darkfighter)</b><br><br>   | <br><br>     | <b>8M ColorVu+ Hybrid Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.0, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>-U: Built-in microphone                      | <b>426</b>      |
| <b>YENİ</b><br><br><b>DS-2CD2T87G3-LIS2UY/SL</b><br><b>(Darkfighter)</b><br><br> | <br><br> | <b>8M ColorVu+ Hybrid Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.0, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;                                               | <b>494</b>      |
| <b>DS-2CD2683G2-LI2S2U</b><br><b>(Power By Darkfighter)</b><br><br>              |                                                                                             | <b>8MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;<br>3000K Warm LED; EXIR, up to 60m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>Audio/Alarm IO; Built-in Dual-Array Microphone | <b>498</b>      |
| <b>DS-2CD2783G2-LI2S2U</b><br><b>(Power By Darkfighter)</b><br><br>              |                                                                                             | <b>8MP Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;<br>20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;<br>3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>Audio/Alarm IO; Built-in Dual-Array Microphone   | <b>498</b>      |

| ÜRÜN KODU<br>(Model Number)                                                                                                                            | RESİM<br>(Picture)                                                                                                                                                         | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Liste<br>(MSRP) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br>DS-2CD2686G2HT-IZS2U/SL<br>(Darkfighter)<br><br>   | <br>     | <b>8MP Motorize Varifokal Lensli IR Bullet Kamera<br/>Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*Junction box is included in the camera package | <b>646</b>      |
| <b>YENİ</b><br><br>DS-2CD2786G2H-IPTRZS<br>(Darkfighter)<br><br>      | <br>     | <b>8MP Motorize Varifokal Lensli IR Dome Kamera<br/>Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; PTRZ</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>*Junction box is included in the camera package         | <b>566</b>      |
| <b>YENİ</b><br><br>DS-2CD2687G3-LIZS2UY/SL<br>(Darkfighter)<br><br> | <br>  | <b>8MP Colorvu Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR &amp; Live Guard</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;                                 | <b>752</b>      |
| <b>YENİ</b><br><br>DS-2CD2787G3T-LIZSY<br>(Darkfighter)<br><br>     | <br> | <b>8MP Colorvu Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b><br>1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light<br>25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;                                                    | <b>752</b>      |
| <b>Panoramic &amp; Live Guard Cameras</b>                                                                                                              |                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |
| <b>YENİ</b><br><br>DS-2CD2T46G2P-LSU/SL<br><br>                     | <br> | <b>2*4MP Panoramic &amp; Live Guard Cameras<br/>Strobe light &amp; Audio</b><br>2*1/2.5" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.003 lux @ (F1.6, AGC ON), 0 lux with IR;<br>20fps(3632×1632); VCA functions; 2 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;<br>Built-in microphone and speaker, Audio/Alarm I/O;<br>180° FOV                                                                                                       | <b>277</b>      |

| ÜRÜN KODU<br>(Model Number)                                                                                      | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                   | Liste<br>(MSRP) |
|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                                                                                      |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CD2T47G2P-LSU/SL</b><br> |    | <b>2 4MP Colorvu Panoramic &amp; Live Guard Cameras</b><br><b>2*1/1.8" Progressive Scan CMOS; Strobe light &amp; Audio</b><br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;<br>20fps(5120×1440),VCA functions; 2 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC<br>slot; HIK-Connect cloud service;<br>Built-in microphone and speaker, Audio/Alarm I/O;180° FOV                   | <b>369</b>      |
| <b>YENİ</b>                                                                                                      |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CD2T87G2P-LSU/SL</b><br> |    | <b>2 8MP Colorvu Panoramic &amp; Live Guard Cameras</b><br><b>Strobe light &amp; Audio</b><br>2*1/1.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;<br>20fps(5120×1440),VCA functions; 2 streams; 3D DNR; BLC; ICR;<br>3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC<br>slot; HIK-Connect cloud service;<br>Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV               | <b>448</b>      |
| <b>Balıkgözü KAMERA</b>                                                                                          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CD2955G0-ISU</b><br>   |    | <b>5MP Balıkgözü KAMERA</b><br>1/2.9" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.016 lux@(F2.2, AGC ON), 0 lux with IR;<br>25fps/30fps(2560×1920, 2048×1536, 1920×1080); F2.2, field of<br>view: 180°(H)×180°(V); 120dB WDR; 2 streams; 3D DNR; BLC;<br>ICR; EXIR, up to 8m; DC12V&PoE; Built-in micro SD/SDHC/SDXC<br>slot; HIK-Connect cloud service<br>build-in-mic                                                                   | <b>334</b>      |
| <b>HeatPro Termal KAMERA</b>                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2TD2617-6/QA</b><br>    |  | <b>4MP optical Bullet Thermal Kamera</b><br>160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C,<br>F# = 1.1) High accuracy temperature exception alarm, -20 °C to<br>150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F)<br>Image processing technology: linear, histogram, self-adaptive<br>thermal AGC mode, DDE, 3D DNR Support smoking detection<br>algorithm<br>Support sun-reflection filter;Focal Length 6.2 mm                                               | <b>836</b>      |
| <b>DS-2TD2617-3/QA</b><br>    |  | <b>4MP optical Bullet Thermal Kamera</b><br>160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C,<br>F# = 1.1) High accuracy temperature exception alarm, -20 °C to<br>150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F)<br>Image processing technology: linear, histogram, self-adaptive<br>thermal AGC mode, DDE, 3D DNR Support smoking detection<br>algorithm<br>Support sun-reflection filter;Focal Length 3.1 mm                                               | <b>794</b>      |
| <b>DS-2TD2628-3/QA</b><br>    |  | <b>4MP optical Bullet Thermal Kamera</b><br>256 × 192 resolution, 12 μm, VOx UFPA, NETD < 40 mK (25°C,<br>F1.0)<br>Video content analysis: vehicle/human classification<br>Temperature exception alarm for fire prevention, -20°C to 150°C (-<br>4°F to 302°F), ± 8°C (± 14.4°F) Support smoking detection<br>algorithm<br>Support sun-reflection filter algorithm<br>Image processing technology: linear, histogram, self-adaptive<br>thermal AGC mode, DDE, 3D DNR | <b>988</b>      |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| PTZ KAMERALAR               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                 |
| IP PTZ KAMERA               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                 |
| DS-2DE2C400MWG-E            |    | <b>4 MP Network IR 2-inch PT Dome (H.265+, 30m IR)</b><br>1/2.7" Progressive Scan CMOS<br>Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR<br>2.8 mm, horizontal FOV 94°, vertical FOV 49°, diagonal FOV 114°<br>4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85°<br>White Light Distance: up to 30 m IR Distance: up to 30 m<br>Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker, audible warning when alarm triggers, POE                                                                                                                    | 152             |
| DS-2DE2C400SCG-E            |    | <b>4 MP Network ColorVu 2-inch live guard PT Dome (H.265+, 30m IR)</b><br>1/2.8" Progressive Scan CMOS 2560 × 1440<br>Color: 0.001 Lux @(F1.0, AGC ON), B/W: 0 Lux with IR<br>2.8 mm, horizontal FOV 105.7°, vertical FOV 57.3°, diagonal FOV 124.9°<br>4 mm, horizontal FOV 88.7°, vertical FOV 44.7°, diagonal FOV 107.5°<br>White Light Distance: up to 30 m<br>Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker                                                                                                                                           | 239             |
| DS-2SE2C400MWG-E/14         |  | <b>4MP Dual-lens, 2 inch live guard PT Dome, 30m IR)</b><br><ul style="list-style-type: none"> <li>· Capture a large area and details at the same time</li> <li>· Support Human and Vehicle detection</li> <li>· Smart Hybrid Light: advanced technology with long range</li> <li>· Hik-Connect cloud service and app for remote management and views of devices</li> <li>· Built-in microphone and speaker for real-time audio security</li> <li>· Built-in memory card slot, support microSD/SDHC/SDXC card, up to 512 GB</li> <li>· Water and dust resistant (IP66)</li> </ul> | 239             |
| DS-2DE4215IW-DE             |  | <b>2MP Network Dış Ortam IR PTZ Kamera, Deep learning</b><br>1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 15× optical zoom and 16× digital zoom provide close up views over expansive areas. WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus<br>Expansive night view with up to 100 m IR distance<br>Support H.265+/H.265 video compression                                                                                                               | 623             |
| DS-2DE4425IW-DE             |  | <b>4MP Network Dış Ortam IR PTZ Kamera</b><br>1/2.8" progressive scan CMOS. High quality imaging with 4 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 25× optical zoom and 16× digital zoom provide close up views over expansive areas<br>WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus<br>Expansive night view with up to 100 m IR distance<br>Support H.265+/H.265 video compression                                                                                                                           | 756             |



| ÜRÜN KODU<br>(Model Number)                           | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Liste<br>(MSRP) |
|-------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-2SE4C425MWG-E/RB/14<br><br>ColorVu AcuSense        |    | <b>4MP Bullet lens:4MP, 30m White Light PTZ lens</b><br>Captures a large area and great details at the same time<br>· High quality imaging with 4 MP resolution<br>· Focuses on human and vehicle targets classification based on deep learning<br>· Excellent low-light performance with powered-by-DarkFighter technology and ColorVu technology<br>· Secures an expansive area with 25 × optical zoom and 16 × digital zoom<br>· Expansive night view with up to 100 m IR distance & 30 m white light<br>· Build-in speaker and dual-microphone for real-time high quality audio security<br>· Active strobe light and audio alarm to warn intruders off<br>· Supports 12 VDC & PoE+ | 859             |
| DS-2SE4C425MWG-E/26(F0)<br><br>ColorVu AcuSense       |    | <b>4MP Network Dış Ortam IR PTZ Kamera</b><br>Captures a large area and great details at the same time<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Secures an expansive area with 25× optical zoom and 16× digital zoom<br>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus<br>Expansive night view with up to 200 m IR distance<br>Supports 24 VAC & Hi-PoE<br>Active strobe light and audio alarm to warn intruders off                                                                                                                                            | 946             |
| DS-2DE7A432MWG-EB<br><br>AcuSense                     |  | <b>4MP Network Dış Ortam IR PTZ Kamera, Deep learning</b><br>1/1.8" progressive scan CMOS<br>Up to 2560 × 1440@30fps resolution<br>Min. illumination:<br>Color: 0.0005 Lux @(F1.2, AGC ON)<br>B/W: 0.0001 Lux @(F1.2, AGC ON)<br>0 Lux with IR<br>32× optical zoom, 16× digital zoom<br>WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus<br>White light: up to 100 m / IR: up to 150 m<br>24 VAC & Hi-PoE<br>Support H.265+/H.265 video compression<br>Support audio visual alarm                                                                                                                                                                                   | 1410            |
| YENİ<br><br>DS-2SE7C432MWG-EB<br><br>ColorVu AcuSense |  | <b>4MP Network Dış Ortam IR PTZ Kamera ( 32X, 200m IR, IP66, deep learning)</b><br>Captures a large area and great details at the same time<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Secures an expansive area with 32× optical zoom and 16× digital zoom<br>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus<br>Expansive night view with up to 200 m IR distance<br>Supports 24 VAC & Hi-PoE<br>Active strobe light and audio alarm to warn intruders off                                                                                                       | 1524            |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>WIFI Camera</b>          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2CV2021G2-IDW</b>     |    | <b>2MP Wi-Fi Bullet Camera</b><br>1/2.8" Progressive CMOS, ICR, 0lux with IR,<br>1920x1080/1280x720: 25fps(P)/30fps(N), 2.8/4mm lens,<br>H.265+/H.265/H.264+/H.264/MJPEG, dual-stream, 3D<br>DNR,support on-board storage up to 256GB(SD card slot), Build-in<br>microphone and speaker, Build-in external Dual-Antenna 2.4GHz<br>Wi-Fi, 802.11b/g/n.<br>*power supply included;*SD Card not included<br>*(W) version models support mobile monitoring via Hik-Connect                     | <b>91</b>       |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2CV2041G2-IDW</b>     |    | <b>4MP Wi-Fi Bullet Camera</b><br>1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1440:30fps,<br>2304x1296/1920x1080/1280x720: 25fps(P)/30fps(N),<br>H.265+/H.264+/H.264/MJPEG, Dual-stream, WDR, 3D DNR,<br>support on-board storage up to 256GB(SD card slot), Build-in<br>microphone and speaker, Build-in external Dual-Antenna 2.4GHz<br>Wi-Fi, 802.11b/g/n.*power supply included<br>*SD Card not included<br>*(W) version models support mobile monitoring via Hik-Connect           | <b>128</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2CV2Q21G1-IDW</b>     |    | <b>2MP Wi-Fi Indoor PT camera</b><br>1/2.8" Progressive CMOS, ICR,1920x1080: 25fps(P)/30fps(N),<br>H.265+/H.265,3D DNR, support on-board storage up to 256GB,<br>Build-in microphone and speaker, two-way talk, support two-way<br>audio, Support mobile monitoring via Hik-Connect<br>5VDC power supply is included.                                                                                                                                                                      | <b>84</b>       |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2DE2C200IWG/W</b>     |  | <b>2MP Wi-Fi outdoor PT camera</b><br>1/2.7" Progressive Scan CMOS<br>Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR<br>2.8 mm, horizontal FOV 105°, vertical FOV 58°, diagonal FOV<br>123°<br>4 mm, horizontal FOV 81°, vertical FOV 44°, diagonal FOV 97°<br>IR Distance: up to 30 m<br>Digital WDR, BLC, HLC, 3D DNR,Built-in Microphone,Built-in<br>Speaker,audible warning when alarm triggers;Wi-Fi Connection                                                                  | <b>124</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2DE2C400IWG/W</b>     |  | <b>4MP Wi-Fi outdoor PT camera</b><br>1/2.7" Progressive Scan CMOS<br>Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR<br>2.8 mm, horizontal FOV 94°, vertical FOV 49°, diagonal FOV 114°<br>4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85°<br>IR Distance: up to 30 m<br>Digital WDR, BLC, HLC, 3D DNR,Built-in Microphone,Built-in<br>Speaker,audible warning when alarm triggers;Wi-Fi Connection                                                                      | <b>161</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-2CD2423G2-IW</b>      |  | <b>2MP Wi-Fi Cube Camera</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG; Color:0 lux with IR;<br>25Fps/30fps(1920x1080); 2 streams; DWDR; 3D DNR; ICR;<br>EXIR, up to 10m; support AI human body detection; support on-<br>board storage up to 512GB(SD card slot), Hik-Connect cloud<br>service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi,<br>802.11b/g/n; 12VDC & PoE power supply.<br>*SD card is not included.<br>*Power supplier is not included | <b>84</b>       |

| ÜRÜN KODU<br>(Model Number)       | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                        | Liste<br>(MSRP) |
|-----------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                       |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |
| <b>DS-2CD2443G2-IW</b>            |    | <b>4MP Wi-Fi Cube Camera</b><br>1/2.8" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG; Color: 0 lux with IR;<br>20Fps0(2560×1440); 2 streams; DWDR; 3D DNR; ICR; EXIR, up to 10m; support AI human body detection; support on-board storage up to 512GB(SD card slot), Hik-Connect cloud service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi, 802.11b/g/n; 12VDC & PoE power supply.<br>*SD card is not included.<br>*Power supplier is not included | <b>113</b>      |
| <b>Solar Kamera</b>               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |
| <b>DS-2DE2C200IWG-K/4G/C05S10</b> |    | <b>2MP 4G Solar PT Camera</b><br>2MP,1920x1080,4G Connection<br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Built-in mic & speaker for two-way audio<br>Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m<br>Built-in 8 GB eMMC storage ;<br>IP66 for protection against dust and water<br>Solar panel: 10 W, battery: 50 Wh<br>36-hour continuous power supply in proactive mode on cloudy or rainy days       | <b>388</b>      |
| <b>DS-2DE2C400IWG-K/4G/C05S10</b> |  | <b>4MP 4G Solar PT Camera</b><br>4MP,2560x1440,4G Connection<br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Built-in mic & speaker for two-way audio<br>Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m<br>Built-in 8 GB eMMC storage ;<br>IP66 for protection against dust and water<br>Solar panel: 10 W, battery: 50 Wh<br>36-hour continuous power supply in proactive mode on cloudy or rainy days       | <b>429</b>      |
| <b>DS-2DE2C200IWG-K/4G/C09S20</b> |  | <b>2MP 4G Sola PT Camera</b><br>2MP,1920x1080,4G Connection<br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Built-in mic & speaker for two-way audio<br>Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m<br>Built-in 8 GB eMMC storage ;<br>IP66 for protection against dust and water<br>Solar panel: 20 W, battery: 90 Wh<br>72-hour continuous power supply in proactive mode on cloudy or rainy days        | <b>471</b>      |

| ÜRÜN KODU<br>(Model Number)   | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-2DE2C400IWG-K/4G/C09S20    |    | <b>4MP,2560x1440,4G Connection</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Built-in mic & speaker for two-way audio<br>Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m<br>Built-in 8 GB eMMC storage ;<br>IP66 for protection against dust and water<br>Solar panel: 20 W, battery: 90 Wh<br>72-hour continuous power supply in proactive mode on cloudy or rainy days                                                                                                                  | 517             |
| DS-2XS2T41G1-ID/4G/C05S07     |    | <b>4MP 4G Sola Bullet Camera</b><br>1/3" Progressive Scan CMOS;<br>H.265+/H.265/H.264+/H.264/MJPEG;<br>Color: 0.005 lux @(F1.0, AGC ON), 0 lux with LED on;<br>12.5fps/15fps(2560x1440, 1920x1080); 2 streams; 3D DNR; BLC;<br>ICR; EXIR LED; Solar panel & 5VDC; Built-in 8 GB eMMC storage (6 GB available for recording); Built-in memory card slot, support microSD/SDHC/SDXC card up to 256 GB; Build-in microphone and speaker; Build-in PIR + Radar, up to 10m; Support working between 0 °C to 40 °C (32 °F to 104 °F); Hik-Connect cloud service; | 388             |
| NETWORK VIDEO KAYIT CİHAZLARI |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| 4 KANAL NVR                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| DS-7104NI-Q1                  |  | <b>4 Kanal Q Serial mini NVR (1 SATA, H.265)</b><br>40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Plastic)                                                                                                                                                                                                                                                                                                                                                                                                               | 106             |
| DS-7104NI-Q1/4P               |  | <b>4 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b><br>40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Plastic)                                                                                                                                                                                                                                                                                                                                                                     | 179             |
| DS-7104NI-Q1/M                |  | <b>4 Kanal Q serial mini NVR (1 SATA, H.265)</b><br>40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Metal)                                                                                                                                                                                                                                                                                                                                                                                                                 | 117             |
| DS-7104NI-Q1/4P/M             |  | <b>4 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b><br>40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Metal)                                                                                                                                                                                                                                                                                                                                                                       | 190             |
| DS-7604NI-Q1(STD)(D)          |  | <b>4 Kanal Q serial NVR (1 SATA, H.265)</b><br>4-channels Motion Detection 2.0<br>40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case                                                                                                                                                                                                                                                                                                                                                                                          | 172             |
| DS-7604NI-Q1/4P(STD)(D)       |  | <b>4 Kanal Q serial NVR (1 SATA, H.265, POE)</b><br>4-channels Motion Detection 2.0<br>40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case                                                                                                                                                                                                                                                                                                                                                                                     | 248             |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                           | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>8 KANAL NVR</b>          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                 |
| <b>DS-7108NI-Q1</b>         |    | <b>8 Kanal Q serial mini NVR (1 SATA, H.265 )</b><br>60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)                                                                                                                                                                                                                                                                                                                                                | <b>128</b>      |
| <b>DS-7108NI-Q1/8P(D)</b>   |    | <b>8 Kanal Q serial mini NVR (1 SATA, H.265, POE )</b><br>60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)                                                                                                                                                                                                                                                                                                                                           |                 |
| <b>DS-7108NI-Q1/M</b>       |    | <b>8 Kanal Q serial mini NVR (1 SATA, H.265 )</b><br>60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Metal)                                                                                                                                                                                                                                                                                                                                                  | <b>135</b>      |
| <b>DS-7108NI-Q1/8P/M</b>    |    | <b>8 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b><br>60Mbps Bit Rate Input Max (up to 8-ch IP video) 1 SATA interface, 8 independent PoE network interfaces, mini 1U case(Metal)                                                                                                                                                                                                                                                                                                         | <b>266</b>      |
| <b>DS-7608NI-Q1</b>         |    | <b>8 Kanal Q serial NVR (1 SATA, H.265)</b><br>4-channels Motion Detection 2.0<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case                                                                                                                                                                                                                                                                                       | <b>186</b>      |
| <b>DS-7608NI-Q1/8P</b>      |    | <b>8 Kanal Q serial NVR (1 SATA, H.265, POE)</b><br>4-channels Motion Detection 2.0<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case                                                                                                                                                                                                                                                                                  | <b>325</b>      |
| <b>DS-7608NI-Q2</b>         |  | <b>8 Kanal Q serial NVR (2 SATA, H.265)</b><br>4-channels Motion Detection 2.0<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case                                                                                                                                                                                                                                                                                      | <b>245</b>      |
| <b>DS-7608NI-Q2/8P</b>      |  | <b>8 Kanal Q serial NVR (2 SATA, H.265, POE)</b><br>4-channels Motion Detection 2.0<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case                                                                                                                                                                                                                                                                                 | <b>394</b>      |
| <b>DS-7608NXI-K2</b>        |  | <b>8 kanal K series AcuSense NVR (2 SATA ,4K &amp; H.265)</b><br>All-channels Motion Detection 2.0<br>Facial Recognition for up to 4 channels picture stream or 1 channels video stream;<br>* Facial recognition and Motion Detection 2.0 cannot be enabled at the same time.<br>Support 16 face libraries, up to 20,000 face pictures in total;<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1                                          | <b>296</b>      |
| <b>DS-7608NXI-K2/8P</b>     |  | <b>8 kanal K series AcuSense NVR (2 SATA 4K &amp; H.265,POE)</b><br>All-channels Motion Detection 2.0<br>Facial Recognition for up to 4 channels picture stream or 1 channels video stream;<br>* Facial recognition and Motion Detection 2.0 cannot be enabled at the same time.<br>Support 16 face libraries, up to 20,000 face pictures in total;<br>80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1 | <b>496</b>      |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                    | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7608NI-M2</b>         |    | <b>8 Kanal M seral 8K NVR (2 SATA, 8K,H.265+ )</b><br>8-ch 1U 8K NVR<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 8-ch IP camera inputs<br>Up to 8-ch@8 MP decoding capacity<br>Up to 128 Mbps incoming bandwidth<br>Up to 8-ch IP speakers can be connected   | <b>529</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7608NI-M2/8P</b>      |    | <b>8 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE)</b><br>128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDML up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case                             | <b>741</b>      |
| <b>16 KANAL NVR</b>         |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7616NI-Q2</b>         |    | <b>16 Kanal Q serial NVR (2 SATA, H.265 )</b><br>160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case                                                                                                                                    | <b>270</b>      |
| <b>DS-7616NI-Q2/16P</b>     |    | <b>16 Kanal Q serial NVR (2 SATA, H.265,POE )</b><br>160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case                                                                                         | <b>511</b>      |
| <b>DS-7616NXI-K2</b>        |   | <b>16 Kanal K serial Acusense NVR (2 SATA,4k&amp;H.265)</b><br>Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs       | <b>372</b>      |
| <b>DS-7616NXI-K2/16P</b>    |  | <b>16 Kanal K serial Acusense NVR (2 SATA, 4K&amp;H.265, POE)</b><br>Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs | <b>672</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7616NI-M2</b>         |  | <b>16 Kanal M serial 8K NVR (2 SATA, 8K &amp; H.265+ )</b><br>128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDML up to 8K, 2 SATA Interfaces, alarm I/O: 4/1, 380 1U case                                                                 | <b>642</b>      |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7616NI-M2/16P</b>     |  | <b>16 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE)</b><br>128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDML up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case                            | <b>1011</b>     |
| <b>32 KANAL NVR</b>         |                                                                                     |                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7632NXI-K2</b>        |  | <b>32 Kanal K serial Acusense NVR (2 SATA, 4K&amp;H.265)</b><br>Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity<br>Up to 256 Mbps incoming bandwidth                                                                                      | <b>485</b>      |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-7732NXI-K4               |    | <b>32 Kanal K serial Acusense NVR (4SATA, 4K&amp;H.265)</b><br>Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity<br>Up to 256 Mbps incoming bandwidth                                                                                                                                                                                                                                                                                                                                                                                                                                            | 783             |
| DS-7732NXI-I4               |    | <b>32 Kanal I serial Acusense NVR (4SATA, 4K&amp;H.265+)</b><br>False alarm reduction for up to 4-ch 1080P;<br>Facial Recognition for up to 4 channels picture stream or 1 channels video stream;<br>* Facial recognition and perimeter protection cannot be enabled at the same time.<br>Support 16 face libraries, up to 10,000 face pictures in total;<br>256Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 2 HDMI outputs, 1 VGA port, 1 CVBS output, 1 eSATA, alarm I/O: 16/9, 1.5U case, 19"                                                                                                      | 1212            |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| DS-7732NI-M4                |    | <b>32 Kanal M serial 8K NVR (4 SATA, 8K &amp; H.265+)</b><br>320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 4 SATA Interfaces, 2 HDMI outputs(up to 8K), 1 eSATA, alarm I/O: 16/9 1.5U case, 19"                                                                                                                                                                                                                                                                                                                                                                                            | 1189            |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| DS-8632NXI-I8/S             |   | <b>32 Kanal I serial Acusense NVR (8 SATA, Raid, H.265+)</b><br>320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI outputs(up to 4K), 1 eSATA, alarm I/O: 16/9 2U case, 19"                                                                                                                                                                                                                                                                                                                                                                                           | 1843            |
| <b>64 KANAL NVR</b>         |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| DS-7764NI-M4                |  | <b>64 Kanal M serial 8K NVR (4 SATA, 8K&amp;H.265+)</b><br>Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080p decoding capacity; Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth; 2 HDMI and 1 VGA interfaces, 8K or dual 4K video outputs                                                                                                                                                                                                                                                                                                                                          | 1406            |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| DS-8664NXI-I8/S             |  | <b>64 Kanal I Sereil Acusense NVR (8 SATA, Raid, H.265+)</b><br>320Mbps Bit Rate Input Max(up to 64-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI outputs(up to 4K), 1 eSATA<br>alarm I/O: 16/9 2U case, 19"                                                                                                                                                                                                                                                                                                                                                                                         | 2576            |
| <b>DeepInmind NVR</b>       |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>YENİ</b>                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| iDS-7716NXI-M4/X            |  | <b>16 Kanal M Sereil DeepInmind NVR (4 SATA, H.265+, DeepLearning Feature, Large Model algorithm)</b><br>256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD, alarm I/O: 16/8, 1.5U case, 19"<br>Facial Recognition for up to 16 channels picture stream or 16 channels video stream; Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total.<br>Video Structuralization for up to 12-ch video analysis.<br>False alarm filtering for up to 16-ch behavior detection (line crossing, intrusion, region entrance and region exiting) | 2223            |

| ÜRÜN KODU<br>(Model Number)             | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Liste<br>(MSRP) |
|-----------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| iDS-7732NXI-M4/X                        |    | <b>32 Kanal M Sereil DeepMind NVR (4 SATA,H 265+,Deepleaning Feature, Large Model algorithm)</b><br>256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD,alarm I/O: 16/8, 1.5U case,19"<br>Facial Recognition for up to 16 channels picture stream or 16 channels video stream;Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total.<br>Video Structuralization for up to 12-ch video analysis.<br>False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting) | <b>2527</b>     |
| <b>HD-TVI ÜRÜNLER (HD-TVI PRODUCTS)</b> |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>2MP HD TVI KAMERA 4X1</b>            |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| DS-2CE16D0T-EXLPF                       |    | <b>Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera</b><br>High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging<br>One port for 4 switchable signals (TVI/AHD/CVI/CVBS)                                                                                                                                                                                                                                                                                | <b>37</b>       |
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| DS-2CE76D0T-EXLPF                       |  | <b>1080p Mini IR Dome Smart Hybrid Light Kamera</b><br>High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging<br>One port for 4 switchable signals (TVI/AHD/CVI/CVBS)                                                                                                                                                                                                                                                                                         | <b>37</b>       |
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| DS-2CE16D0T-LPFS<br>(Dahili mikrofon)   |  | <b>Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera</b><br>High quality imaging with 2 MP, 1920×1080 resolution<br>2.8 mm, 3.6 mm fixed focal lens<br>Up to 25 m IR distance for bright night imaging<br>Up to 20 m white light distance for bright night imaging<br>One port for four switchable signals (TVI/AHD/CVI/CVBS)<br>High quality audio with audio over coaxial cable, built-in mic<br>Water and dust resistant (IP67)<br>Smart-Hybrid light, optimize your security with flexible lighting options                                                                                              | <b>44</b>       |
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| DS-2CE76D0T-LPFS<br>(Dahili mikrofon)   |  | <b>1080p Mini IR Dome Smart Hybrid Light Kamera</b><br>High quality imaging with 2 MP, 1920×1080 resolution<br>2.8 mm, 3.6 mm fixed focal lens<br>Up to 20 m IR distance for bright night imaging<br>Up to 20 m white light distance for bright night imaging<br>High quality audio with audio over coaxial cable, built-in mic<br>One port for four switchable signals (TVI/AHD/CVI/CVBS)<br>Smart-Hybrid light, optimize your security with flexible lighting options                                                                                                                                          | <b>44</b>       |
| <b>YENİ</b>                             |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| DS-2CE10DF0T-PF<br><br>ColorVu          |  | <b>Harici 1080p IR Bullet Kamera (ColorVu )</b><br>2M CMOS Sensor, Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens,24H Color, Support TVI/AHD/CVI/CVBS video signal output                                                                                                                                                                                                                                                                                                                                                                     | <b>51</b>       |

| ÜRÜN KODU<br>(Model Number)                   | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                   | Liste<br>(MSRP) |
|-----------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE10DF0T-LPFS</b><br>(Dahili mikrofon) |    | <b>Harici 1080p IR Bullet Kamera (ColorVu&amp; Smart Hybrid Light)</b><br>High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)       | <b>58</b>       |
| <b>ColorVu</b>                                |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE70DF0T-LPFS</b><br>(Dahili mikrofon) |    | <b>Dahili/Harici 1080p IR Dome Kamera (ColorVu &amp; Smart Hybrid Light)</b><br>High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS) | <b>58</b>       |
| <b>ColorVu</b>                                |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE12DF0T-LFS</b><br>(Dahili mikrofon)  |    | <b>Dahili/Harici 1080p IR Bullet Kamera (ColorVu &amp; 40m Smart Hybrid Light)</b><br>2M CMOS Sensor, Outdoor smart hybrid light Bullet, 0.001Lux/F1.0, 40m IR+40m White Light, 3D DNR, 12 VDC, Built-in Mic, Audio up Coaxial(Only TVI), OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens, 24H Color, <b>Smart Lighting (With Acusense DVR)</b> , Support TVI/AHD/CVI/CVBS video signal output                                                                         | <b>78</b>       |
| <b>ColorVu</b>                                |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE18D0T-LFS</b>                        |  | <b>2MP Smart Hybrid Light AOC Lamp Camera(40m IR+60m White Light+ IP67)</b><br>2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, Lamp looking, 40m IR+60m White Light, Outdoor Lamp Cam, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens, Support TVI/AHD/CVI/CVBS video signal output                                                 | <b>97</b>       |
|                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>3K(5MP 16:9)) HD TVI KAMERA</b>            |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE16K0T-LPFS</b><br>(Dahili mikrofon)  |  | <b>Dahili/Harici 3k Hybrid Light Bullet Kamera (20mt, Metal)</b><br>3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 25m IR+20m White Light, Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output                                                                     | <b>62</b>       |
|                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                 |
| <b>DS-2CE76K0T-LPFS</b><br>(Dahili mikrofon)  |  | <b>Dahili/Harici 3k Hybrid Light Dome Kamera (20mt, Plastik)</b><br>3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 20m IR+20m White Light, indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output                                                                            | <b>62</b>       |

| ÜRÜN KODU<br>(Model Number)                   | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                       | Liste<br>(MSRP) |
|-----------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>DS-2CE10KF0T-LPFS</b><br>(Dahili mikrofon) |    | <b>Dahili/Harici 3k Hybrid Light Bullet Kamera</b><br>3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), Outdoor smart hybrid light mini Bullet, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output                 | <b>77</b>       |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>DS-2CE70KF0T-LPFS</b><br>(Dahili mikrofon) |    | <b>Dahili/Harici 3k Hybrid Light Dome Kamera</b><br>3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), Indoor smart hybrid light Turret, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output                               | <b>77</b>       |
| <b>HD-TVI KAYIT CİHAZLARI (HD-TVI DVR)</b>    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>4 KANAL TURBO HD DVR</b>                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>DS-7104HGHI-M1</b>                         |    | <b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, mini 1U case                                                                                                                                                                                             | <b>91</b>       |
| <b>DS-7204HGHI-M1</b>                         |   | <b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, 260 1U case                                                                                                                                                                                              | <b>102</b>      |
| <b>iDS-7104HQHI-M1/S</b>                      |  | <b>4 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b><br>2-ch perimeter protection, 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 2-ch IP video input(up to 6-ch IP), 1 SATA interface Live view: 3K Lite@20fps/ch, up to 3K Lite@12fps/ch encoding capability, mini 1U case                                                                | <b>135</b>      |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>DS-7104HGHI-M1/T</b>                       |  | <b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite, Two-way Audio)</b><br>Support HDTV Two-way Audio technology, full-channel motion detection 2.0, 4 Turbo HD/AHD/Analog interface input, 4-ch HDTV coaxial video&audio input, 1-ch IP video input (up to 5-ch), 1-ch RCA audio input, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case | <b>102</b>      |
| <b>YENİ</b>                                   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                          |                 |
| <b>DS-7204HGHI-M1/T</b>                       |  | <b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite, Two-way Audio)</b><br>Support HDTV Two-way Audio technology, full-channel motion detection 2.0, 4 Turbo HD/AHD/Analog interface input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch), 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case  | <b>113</b>      |

| ÜRÜN KODU<br>(Model Number)                                                                                     | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                  | Liste<br>(MSRP) |
|-----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                 |
| <b>iDS-7204HQHI-M1/XT</b><br>  |    | <b>4 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b><br><b>TVI İki Yönlü Sesi Destekleyin DVR</b><br>Support TVI Two-way Audio, 1-ch facial recognition or 2-ch advanced model perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case | <b>157</b>      |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                 |
| <b>iDS-7204HUHI-M1/T</b><br>   |    | <b>4 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP)</b><br>Support TVI Two-way Audio,4-ch false alarm filter,4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 4-ch IP video input(up to 8-ch IP), 1 SATA interface, H.265/H.265+ compression,Live view: 3K @20fps/ch,up to 8MP@8fps(CH1),3K @12fps/ch encoding capability, 260 1U case                                                | <b>245</b>      |
| <b>8 KANAL TURBO HD DVR</b>                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                 |
| <b>DS-7108HGHI-M1</b>                                                                                           |    | <b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25(P)/30(N) fps/ch, mini 1U case                                                                                                                                                                                                                   | <b>113</b>      |
| <b>DS-7208HGHI-M1</b>                                                                                           |   | <b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25)/(P30(N) fps/ch, 260 1U case                                                                                                                                                                                                                    | <b>120</b>      |
| <b>iDS-7108HQHI-M1/S</b><br> |  | <b>8 Kanal HD-TVI Hibrit Kayıt Cihazı (5MP Lite)</b><br>4-ch perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 4-ch IP video input(up to 12-ch IP),1 SATA interface Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, mini 1U case                                                                                                    | <b>219</b>      |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                 |
| <b>DS-7108HGHI-M1/T</b>                                                                                         |  | <b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b><br>Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input, 8-ch HDTV coaxial video&audio input,2-ch IP video input (up to 10-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case                          | <b>120</b>      |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                 |
| <b>DS-7208HGHI-M1/T</b>                                                                                         |  | <b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b><br>Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input,8-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case                           | <b>131</b>      |


| ÜRÜN KODU<br>(Model Number)                                                                               | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                              | Liste<br>(MSRP) |
|-----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| iDS-7208HQHI-M1/XT<br>   |    | <b>8 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b><br>Support TVI Two-way Audio, 2-ch facial recognition or 4-ch advanced model perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case                           | 245             |
| <b>YENİ</b>                                                                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                 |
| iDS-7208HUHI-M1/T<br>    |    | <b>8 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP)</b><br>Support TVI Two-way Audio,4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,8-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 8-ch IP video input(up to 16-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch,up to 8MP@8fps,3K @12fps/ch encoding capability, 4K UHD output, 260 1U case               | 427             |
| <b>16 KANAL TURBO HD DVR</b>                                                                              |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                 |
| DS-7116HGHI-M1                                                                                            |    | <b>16 Kanal HD-TVI Kayıt Cihazı (1080P lite)</b><br>full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV1 coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, mini 1U case                                                                                                                         | 190             |
| DS-7216HGHI-M1                                                                                            |   | <b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, 260 1U case                                                                                                                          | 204             |
| DS-7116HGHI-M1/T                                                                                          |  | <b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b><br>Support HDTV1 Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV1 coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case | 201             |
| DS-7216HGHI-M1/T                                                                                          |  | <b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b><br>Support HDTV1 Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case  | 215             |
| <b>YENİ</b>                                                                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                 |                 |
| iDS-7216HQHI-M1/XT<br> |  | <b>16 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b><br>Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, standalone 1U case          | 423             |

| ÜRÜN KODU<br>(Model Number)                                                                                     | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Liste<br>(MSRP) |
|-----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>iDS-7216HUHI-M1/T</b><br>   |    | <b>16 Kanal HD-TVI Kayıt Cihazı (8MP)</b><br>Support TVI Two-way Audio, 4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch HDTVI coaxial video&audio input, 1-ch RCA audio input, 16-ch IP video input (up to 32-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch, up to 8MP@8fps, 3K @12fps/ch encoding capability, 4K UHD output, 315 1U case                                                                                     | <b>872</b>      |
| <b>32 KANAL TURBO HD DVR</b>                                                                                    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-7232HGHI-M2</b>                                                                                           |    | <b>32 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b><br>Deep learning based human and vehicle targets classification of Motion Detection 2.0; H.265 Pro+/H.265 Pro/H.265 video compression; HDTVI/AHD/CVI/CVBS/IP video input; Audio via coaxial cable; Up to 18-ch IP camera inputs (up to 5 MP); Up to 1080p Lite@15 fps encoding capability; Max. 1200 m for 720p HDTVI signal                                                                                                                         | <b>584</b>      |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>iDS-7232HQHI-M2/XT</b><br> |    | <b>32 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b><br><b>TVI İki Yönlü Sesi Destekleyen DVR</b><br>Support TVI Two-way Audio, 4-ch facial recognition or 8-ch advanced model perimeter protection, 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input (up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces, Live view: 3K Lite@20fps/ch, up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, 380 1U case | <b>840</b>      |
| <b>Monitör</b>                                                                                                  |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-D5022F2-1V2(EU)</b>                                                                                       |  | <b>21.5 inch FHD Borderless Monitor</b><br>100 Hz refresh rate, more fluid and life-like video<br>Ultra-thin device body with ultra-thin border for 3 sides.<br>8 bit LVDS FHD (1920 × 1080) display.<br>Low blue light design for eye care.<br>Multiple interfaces, including VGA, HDMI, audio out, and built-in speaker.<br>Support VESA wall mount.                                                                                                                                                | <b>220</b>      |
| <b>YENİ</b>                                                                                                     |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-D5024F2-BV2S(EU)</b>                                                                                      |  | <b>23.8 inch FHD Borderless Monitor</b><br>VA technology, 178° ultra-wide view screen.<br>8 bit LVDS FHD (1920 × 1080) display.<br>100 Hz refresh rate, more fluid and life-like video.<br>Ultra-thin device body with ultra-thin border for 3 sides.<br>3D noise reduction.<br>Low blue light design for eye care.<br>Dual interface of HDMI and VGA.<br>Support VESA wall mount.<br>Built-in speaker for audio input.                                                                               | <b>262</b>      |

| ÜRÜN KODU<br>(Model Number)                          | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Liste<br>(MSRP) |
|------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>DS-D5027F2-1P2(EU)</b>                            |    | <b>27 inch FHD Borderless Monitor</b><br>100 Hz refresh rate, more fluid and life-like video.<br>IPS technology for wide, 178° ultra-wide view screen.<br>Ultra-thin device body with ultra-thin border for 3 sides.<br>8 bit LVDS FHD (1920 × 1080) display.<br>3D noise reduction.<br>Low blue light design for eye care.<br>Dual interface of HDMI and VGA.<br>Support VESA wall mount.<br>Data Sheet                                                                                                         | <b>350</b>      |
| <b>YENİ</b>                                          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>DS-D5032F3-1V0S(EU)</b>                           |    | <b>31.5-inch FHD Monitor</b><br>32 inch FHD 75Hz VA Monitor with Speaker<br>VA technology, 178° ultra-wide view screen.<br>8 bit LVDS FHD (1920 × 1080) display.<br>3D noise reduction.<br>Low blue light design for eye care.<br>Dual interface of HDMI and VGA.<br>Support VESA wall mount.                                                                                                                                                                                                                    | <b>483</b>      |
| <b>YENİ</b>                                          |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>DS-D5043F3-1V0S(EU)</b>                           |    | <b>42.5-inch FHD Monitor</b><br>Full HD 1920 × 1080 @60 Hz<br>Wide viewing angle: Horizontal 178°, Vertical 178°.<br>Ultra-thin device body with ultra-thin border for 3 sides.<br>Multiple interfaces: HDMI, VGA, USB<br>Build-in speaker, Audio 5W*2.<br>Low blue light design for eye care.<br>3D noise reduction.<br>Support VESA wall mount.                                                                                                                                                                | <b>787</b>      |
| <b>NETWORK SWITCH</b>                                |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
| <b>DS-3E0106P-E/M</b><br><b>(Unmanaged 100Mbps )</b> |  | <b>4 Port Fast Ethernet Unmanaged POE Switch</b><br>L2, Unmanaged, 4 10/100M RJ45 PoE ports,<br>4 x 10/100Mbps PoE port, and 2 x 10/100Mbps RJ45 port.<br>IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output).<br>IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard.<br>6 KV surge protection for PoE ports.<br>Up to 300 m long-range transmission.<br>Wire-speed forwarding.<br>Store-and-forward switching.<br>Solid high-strength metal shell.<br>Reliable fan-free design.                        | <b>57</b>       |
| <b>DS-3E0310P-E/M</b><br><b>(Unmanaged 100Mbps )</b> |  | <b>8 Port Fast Ethernet Unmanaged POE Switch</b><br>L2, Unmanaged, 8 10/100M RJ45 PoE ports<br>8 x 10/100 Mbps PoE port, and 2 x Gigabit RJ45 port.<br>IEEE 802.3at/af standard for PoE ports (Max. 60 W PoE output).<br>IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standard.<br>6 KV surge protection for PoE ports.<br>Up to 300 m long-range transmission.<br>Wire-speed forwarding.<br>Store-and-forward switching.<br>Solid high-strength metal shell.<br>Reliable fan-free design. | <b>91</b>       |

| ÜRÜN KODU<br>(Model Number)                                 | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>DS-3E0318P-E/M</b><br><b>(Unmanaged 100Mbps )</b>        |    | <b>16 Port Fast Ethernet Unmanaged POE Switch</b><br>L2, Unmanaged, 16 10/100M RJ45 PoE ports<br>Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime.<br>Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters.<br>4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables.<br>6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment.<br>Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.                                  | <b>285</b>      |
| <b>DS-3E0326P-E/M</b><br><b>(Unmanaged 100Mbps )</b>        |    | <b>24 Port Fast Ethernet Unmanaged POE Switch</b><br>L2, Unmanaged, 24 10/100M RJ45 PoE ports<br>Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime.<br>Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters.<br>4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables.<br>6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment.<br>Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.                                  | <b>357</b>      |
| <b>YENİ</b>                                                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3E1106P-EI/M</b><br><b>(Smart Managed EI 100Mbps)</b> |  | <b>4 Port Fast Ethernet Smart POE Switch</b><br><b>Cloud management</b><br>4 × 10/100 Mbps PoE port, 2 × 10/100 Mbps RJ45 port<br>Total PoE Power Budget 45W<br>Support 802.1Q VLAN<br>Support PoE watchdog to detect and restart the cameras that do not respond<br>Support STP/RSTP Loop prevention<br>Support cable detection to locate failure<br>Up to 300 m Long Range PoE Transmission<br>6KV Surge Protection                                                                                                                                                                                                                                                                                                                                                                                                      | <b>68</b>       |
| <b>YENİ</b>                                                 |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3E1310P-EI/M</b><br><b>(Smart Managed EI 100Mbps)</b> |  | <b>8 Port Fast Ethernet POE Switch Smart Managed</b><br><b>Cloud management</b><br>L2, Smart Managed, 8 10/100M RJ45 PoE ports<br>Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime.<br>Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters.<br>4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables.<br>6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment.<br>Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs. | <b>110</b>      |

| ÜRÜN KODU<br>(Model Number)                                                    | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                   | Liste<br>(MSRP) |
|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br><b>DS-3E1318P-EI/M</b><br><b>(Smart Managed EI 100Mbps)</b> |    | <b>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 16 10/100M RJ45 PoE ports<br>16 × 10/100 Mbps PoE port, 1 × Gigabit combo, 1 × Gigabit RJ45 port.<br>IEEE 802.3at/af standard for PoE ports.<br>Network topology management, alarm push, network health monitor.<br>6 KV surge protection for PoE ports.<br>AF/AT camera can reach up to 300 m in extend mode.                                                          | <b>293</b>      |
| <b>YENİ</b><br><br><b>DS-3E1326P-EI/M</b><br><b>(Smart Managed EI 100Mbps)</b> |    | <b>24 Port Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 24 10/100M RJ45 PoE ports<br>24 × 100 Mbps PoE RJ45 ports, 2 × gigabit combos.<br>IEEE 802.3at/af standard for PoE ports.<br>Network topology management, alarm push, network health monitor.<br>6 KV surge protection for PoE ports.<br>AF/AT camera can reach up to 300 m in extend mode.                                                                             | <b>372</b>      |
| <b>YENİ</b><br><br><b>DS-3E1506P-EI/M</b><br><b>(Smart Managed EI Gigabit)</b> |    | <b>4 Port Gigabit Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 4 Gigabit RJ45 PoE ports<br>4 × Gigabit PoE port, 2 × Gigabit RJ45 port<br>Total PoE Power Budget 60W<br>Support 802.1Q VLAN<br>Support PoE watchdog to detect and restart the cameras that do not respond<br>Support STP/RSTP Loop prevention<br>Support cable detection to locate failure<br>Up to 300 m Long Range PoE Transmission<br>6KV Surge Protection           | <b>76</b>       |
| <b>YENİ</b><br><br><b>DS-3E1510P-EI/M</b><br><b>(Smart Managed EI Gigabit)</b> |  | <b>8 Port Gigabit Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 16 Gigabit RJ45 PoE ports<br>8 × Gigabit PoE port, 2 × Gigabit RJ45 port<br>Total PoE Power Budget 60W<br>Support 802.1Q VLAN<br>Support PoE watchdog to detect and restart the cameras that do not respond<br>Support STP/RSTP Loop prevention<br>Support cable detection to locate failure<br>Up to 300 m Long Range PoE Transmission<br>6KV Surge Protection          | <b>125</b>      |
| <b>YENİ</b><br><br><b>DS-3E1518P-EI/M</b><br><b>(Smart Managed EI Gigabit)</b> |  | <b>16 Port Gigabit Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 16 Gigabit RJ45 PoE ports<br>16 × gigabit PoE RJ45 ports, 1 × gigabit RJ45 port, 1 × gigabit fiber optical port<br>Total PoE power budget 130 W<br>Unified cloud management for security systems<br>Network topology at your fingertips<br>Remote troubleshooting<br>Visualized topology management<br>Up to 300 m long-range PoE transmission<br>6 kV surge protection | <b>361</b>      |

| ÜRÜN KODU<br>(Model Number)                                                    | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                          | Liste<br>(MSRP) |
|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br><b>DS-3E1526P-EI/M</b><br><b>(Smart Managed EI Gigabit)</b> |    | <b>24 Port Gigabit Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 24 Gigabit RJ45 PoE ports<br>24 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port<br>Total PoE power budget 230 W<br>Unified cloud management for security systems<br>Network topology at your fingertips<br>Remote troubleshooting<br>Visualized topology management<br>Up to 300 m long-range PoE transmission | <b>502</b>      |
| <b>YENİ</b><br><br><b>DS-3E1506P-EI</b><br><b>(Smart Managed EI Gigabit)</b>   |    | <b>4 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 4 Gigabit RJ45 PoE ports,<br>2 Gigabit RJ45 port, 802.3af/at,<br>PoE power budget 60W,<br>HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog,<br>Max. 300 meter PoE transmission, Desktop/Wall mount                                                                                                                    | <b>91</b>       |
| <b>YENİ</b><br><br><b>DS-3E1510P-EI</b><br><b>(Smart Managed EI Gigabit)</b>   |    | <b>8 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 8 Gigabit RJ45 PoE ports,<br>2 Gigabit RJ45 port, 802.3af/at, PoE power budget 110W,<br>HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog,<br>Max. 300 meter PoE transmission, Desktop/Wall mount                                                                                                                      | <b>179</b>      |
| <b>YENİ</b><br><br><b>DS-3E1518P-EI</b><br><b>(Smart Managed EI Gigabit)</b>   |  | <b>16 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 16 Gigabit RJ45 PoE ports, 1 Gigabit RJ45 port, 1 Gigabit SFP port, 802.3af/at, PoE power budget 230W,<br>HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog, Max. 300 meter PoE transmission, Rack mount                                                                                                              | <b>418</b>      |
| <b>YENİ</b><br><br><b>DS-3E1526P-EI</b><br><b>(Smart Managed EI Gigabit)</b>   |  | <b>24 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 24 Gigabit RJ45 PoE ports, 1 Gigabit RJ45 port, 1 Gigabit SFP port, 802.3af/at, PoE power budget 370W,<br>HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog, Max. 300 meter PoE transmission, Rack mount                                                                                                              | <b>585</b>      |
| <b>YENİ</b><br><br><b>DS-3E1510P-SI</b><br><b>(Smart Managed SI Gigabit)</b>   |  | <b>8 Port Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 8 Gigabit PoE ports, 2 Gigabit SFP ports,<br>802.3af/at, PoE power budget 110W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview                                         | <b>315</b>      |

| ÜRÜN KODU<br>(Model Number)                                                 | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                 | Liste<br>(MSRP) |
|-----------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b><br><br><b>DS-3E1518P-SI</b><br>(Smart Managed SI Gigabit)       |    | <b>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 16 Gigabit PoE ports, 2 Gigabit SFP ports, 802.3af/at, PoE power budget 225W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview | <b>608</b>      |
| <b>YENİ</b><br><br><b>DS-3E1526P-SI</b><br>(Smart Managed SI Gigabit)       |    | <b>24 Port Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 24 Gigabit PoE ports, 2 Gigabit SFP ports, 802.3af/at, PoE power budget 370W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview | <b>760</b>      |
| <b>YENİ</b><br><br><b>DS-3E1528P-SI-24P4F</b><br>(Smart Managed SI Gigabit) |    | <b>24 Port 4 SFP Fast Ethernet POE Switch Smart Managed Cloud management</b><br>L2, Smart Managed, 24 Gigabit PoE ports, 4 Gigabit SFP ports, 802.3af/at, PoE power budget 370W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, DHCP Snooping, ACL, IP&MAC filter based on port, SNMP V1/V2C, Max. 300 meter PoE transmission, Rack mount                                                      | <b>794</b>      |
| <b>YENİ</b><br><br><b>DS-3T0506P</b><br>(Industrial POE Switch)             |  | <b>4 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 120w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount                                                                                                                                                   | <b>524</b>      |
| <b>YENİ</b><br><br><b>DS-3T0510P</b><br>(Industrial POE Switch)             |  | <b>8 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 240w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount                                                                                                                                                   | <b>764</b>      |
| <b>YENİ</b><br><br><b>DS-3T0306HP</b><br>(Industrial POE Switch)            |  | <b>4 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 4 10/100M PoE ports, 1 Gigabit RJ45, 1 Gigabit SFP Uplink, 802.3af/at/bt, port 1 support Hi-PoE 60w, power budget ≤ 110w ( based on power supply, power supply unit not included ), ports 3-4 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -40~75°C, DIN rail                          | <b>106</b>      |
| <b>YENİ</b><br><br><b>DS-3T0310HP</b><br>(Industrial POE Switch)            |  | <b>8 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 8 10/100M PoE ports, 1 Gigabit RJ45, 1 Gigabit SFP Uplink, 802.3af/at/bt, port 1-2 support Hi-PoE 60w, power budget ≤ 110w ( based on power supply, power supply unit not included ), ports 7-8 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -40~75°C, DIN rail                        | <b>179</b>      |

| ÜRÜN KODU<br>(Model Number)                               | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3T0506HP</b><br><b>( (Industrial POE Switch))</b>   |    | <b>4 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 120w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount                                                                                                                                           | <b>460</b>      |
| <b>YENİ</b>                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3T0510HP</b><br><b>(Industrial POE Switch)</b>      |    | <b>8 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 240w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount                                                                                                                                           | <b>676</b>      |
| <b>YENİ</b>                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3T0506HP-E/HS</b><br><b>(Industrial POE Switch)</b> |    | <b>4 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at/bt, port 1 support Hi-PoE 60w, PoE power budget 60W, ports 3-4 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -30~65°C, DIN rail, power supply unit is included by default, industrial power supply optional    | <b>163</b>      |
| <b>YENİ</b>                                               |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                            |                 |
| <b>DS-3T0510HP-E/HS</b><br><b>(Industrial POE Switch)</b> |   | <b>8 Port Fast Ethernet Industrial POE Switch</b><br>L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at/bt, port 1-2 support Hi-PoE 90w, PoE power budget 110W, ports 7-8 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -30~65°C, DIN rail, power supply unit is included by default, industrial power supply optional | <b>281</b>      |
| <b>DS-3E0505D-O</b>                                       |  | <b>5 Port Fast Ethernet Unmanaged Desktop Switch</b><br>L2, Unmanaged, 5 Gigabit RJ45 ports, desktop plastic switch<br>5 x 10/100/1000 Mbps ethernet port<br>Supports ADI/ADIX<br>Store-and-forward switching<br>Supports MAC address auto-learning and aging<br>Simple, compact body design<br>Supports desktop and wall-mounting<br>Plug & play, easy to use.                            | <b>27</b>       |
| <b>DS-3E0508D-O</b>                                       |  | <b>8 Port Fast Ethernet Unmanaged Desktop Switch</b><br>L2, Unmanaged, 8 Gigabit RJ45 ports, desktop plastic switch<br>8 x 10/100/1000 Mbps ethernet ports<br>Supports ADI/ADIX<br>Store-and-forward switching<br>Supports MAC address auto-learning and aging<br>Simple, compact body design<br>Supports desktop and wall-mounting<br>Plug & play, easy to use.                           | <b>46</b>       |
| <b>DS-3E0105D-O</b>                                       |  | <b>5 Port Fast Ethernet Unmanaged Desktop Switch</b><br>L2, Unmanaged, 5 10/100M RJ45 ports, desktop plastic switch<br>5 x 10/100 Mbps ethernet port<br>Supports ADI/ADIX<br>Store-and-forward switching<br>Supports MAC address auto-learning and aging<br>Simple, compact body design<br>Supports desktop and wall-mounting installation<br>Plug & play, easy to use                     | <b>15</b>       |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                    | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-3E0108D-O                |    | <b>8 Port Fast Ethernet Unmanaged Desktop Switch</b><br>L2, Unmanaged, 8 10/100M RJ45 ports, desktop plastic switch<br>5 x 10/100 Mbps ethernet port<br>Supports ADI/ADIX<br>Store-and-forward switching<br>Supports MAC address auto-learning and aging<br>Simple, compact body design<br>Supports desktop and wall-mounting installation<br>Plug & play, easy to use                                | 23              |
| DS-3WF0EC-5ACT              |    | <b>500m Elevator Wireless Bridge kit</b><br>Elevator 5GHz wireless bridge, Max.distance 500m, 2x2 MIMO antenna with 867Mbps throughput, IEEE 802.11ac, Angle H: 50° V: 50°, 2 10/100M RJ45, 2 x 10/100 Mbps RJ45 ports, support Standard PoE input&Output, DFS,TPC                                                                                                                                    | 198             |
| DS-3WF0EC-2NT               |    | <b>200m Elevator Wireless Bridge kit</b><br>Elevator 2.4GHz wireless bridge, Max.distance 500m, 2x2 MIMO antenna with 300Mbps throughput, IEEE 802.11n, Angle H: 65° V: 65°, 2 10/100M RJ45, 2 x 10/100 Mbps RJ45 ports, support 12~24V DC and passive PoE input                                                                                                                                      | 137             |
| DS-3WF0BC-2NT(B)            |   | <b>200m Elevator Wireless Bridge kit</b><br>Elevator 2.4GHz wireless bridge, Max.distance 200m, 1x1 MIMO antenna with 72Mbps throughput, IEEE 802.11n, Angle H: 50° V: 50°, 1 10/100M RJ45, support 12 VDC/1 A, support passive PoE input                                                                                                                                                             | 91              |
| DS-3WF1000-EI-2N            |  | <b>1KM Outdoor Wireless Bridge Kit</b><br>Outdoor 2.4GHz wireless bridge Kit, Max.distance 1km, 2x2 MIMO antenna with 300Mbps throughput, 7dBi gain, 802.11n, Angle H: 60°, 2 100Mbps RJ45 ports, Support 12 VDC or Passive PoE Power supply, Support Web, iVMS-4200, HCP, HPP<br>Tested Throughput at different distance:<br>PTP: 70Mbps/1KM, 90Mbps/500M, 90Mbps/200M<br>PTMP(1 to 4): 40Mbps/1KM   | 110             |
| DS-3WF3000-EI-5AC/P         |  | <b>3KM Outdoor Wireless Bridge Kit</b><br>Outdoor 5GHz wireless bridge Kit, Max.distance 3km, 2x2 MIMO antenna with 867Mbps throughput, 8dBi gain, 802.11n, Angle H: 50°, 2 100Mbps RJ45 ports, support Standard PoE input&Output, Support Web, iVMS-4200, HCP, HPP<br>Tested Throughput at different distance:<br>PTP: 40Mbps/3KM, 90Mbps/1KM, 90Mbps/500M<br>PTMP(1 to 4): 30Mbps/3KM               | 175             |
| DS-3WF02-5AC/D              |  | <b>5KM Outdoor Wireless Bridge Kit</b><br>Outdoor 5GHz wireless bridge CPE, Max.distance 5km, 2x2 MIMO antenna with 867Mbps throughput, 9dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 35°, 2 x 10/100 Mbps RJ45 ports, support Standard PoE input&Output, HPP<br>Tested Throughput at different distance in PTP mode:<br>PTP: 40Mbps/5KM, 90Mbps/1KM, 90Mbps/500M<br>PTMP(1 to 4): 80Mbps/1KM | 220             |

| ÜRÜN KODU<br>(Model Number) | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Liste<br>(MSRP) |
|-----------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-3WF03C-5AC/O             |    | <b>15KM Outdoor Wireless Bridge</b><br>Outdoor 5GHz wireless bridge CPE, Max.distance 15km, 2x2 MIMO antenna with 867Mbps throughput, 12dBi gain, output power 27dBm, 802.11a/n/ac, Angle H: 35°, 1 Gigabit RJ45, 1 Gigabit RJ45 with passive PoE input, TDMA, DFS, TPC, Smart Managed                                                                                                                                                                                                                                     | 156             |
| DS-3WF0FC-2N/O              |    | <b>1KM Outdoor Wireless Bridge</b><br>Outdoor 2.4GHz wireless bridge CPE, Max.distance 1km, 2x2 MIMO antenna with 300Mbps throughput, 7dBi gain, 802.11n, Angle H: 35°, 2 100Mbps RJ45 ports, Support 12 VDC or Passive PoE Power supply, Support Web, iVMS-4200, HCP<br>Point to point: Support up to 4-ch IPC (2MP) in Max. 1 KM distance and Max. 20 Mbps bandwidth<br>Point to multi-point: Support up to 4-ch IPC (2MP) in Max. 1 KM distance and Max. 20 Mbps bandwidth within 35° ± 5°, Max. 1 to 4 PTMP connection | 68              |
| DS-3WF3000S-EI-5AC/P        |    | <b>3KM Outdoor Wireless Bridge</b><br>Outdoor 5GHz wireless bridge CPE, Max.distance 3km, 2x2 MIMO antenna with 867Mbps throughput 8dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 50°, 2 × 10/100 Mbps RJ45 ports, support Standard PoE output                                                                                                                                                                                                                                                                      | 376             |
| DS-3WF02C-5AC/O             |  | <b>5KM Outdoor Wireless Bridge</b><br>Outdoor 5GHz wireless bridge CPE, Max.distance 5km, 2x2 MIMO antenna with 867Mbps throughput, 9dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 35°, 1 Gigabit RJ45, 1 Gigabit RJ45 with passive PoE input, TDMA, DFS, TPC, Smart Managed                                                                                                                                                                                                                                        | 114             |
| DS-3WAP522-SI               |  | <b>Wi-Fi 5 1200M In-Wall Access Point</b><br>1200 Mbps Dual-band Wi-Fi 5 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, Max/Recommend user access is 256/80, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)                                                                                            | 152             |
| DS-3WAP622G-SI              |  | <b>Wi-Fi 6 1800M Ceiling Access Point</b><br>1800 Mbps Dual-band Wi-Fi 6 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)                                                                                           | 232             |
| DS-3WAP622E-SI              |  | <b>Wi-Fi 6 3000M Ceiling Access Point</b><br>3000 Mbps Dual-band Wi-Fi 6 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 2.5G Multi-Giga port with PoE in, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)                                                                                   | 285             |

| ÜRÜN KODU<br>(Model Number)  | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Liste<br>(MSRP) |
|------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-3WAP521-SI                |    | <b>Wi-Fi 5 1200M In-Wall Access Point</b><br>1200 Mbps Dual-band Wi-Fi 5 Gigabit in-Wall indoor AP, 2x2 MIMO, 2 Gigabit port with 1 PoE in, Max/Recommend user access is 128/50, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, 86 mm standard wall junction box                                                                                                                                                                                                                                                                                                                                                     | 152             |
| DS-3WAP621E-SI               |    | <b>Wi-Fi 6 3000M In-Wall Access Point</b><br>3000 Mbps Dual-band Wi-Fi 6 Gigabit in-Wall indoor AP, 2x2 MIMO, 2 Gigabit port with 1 PoE in, Max/Recommend user access is 256/70, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, 86 mm standard wall junction box                                                                                                                                                                                                                                                                                                                                                     | 285             |
| DS-3WAP623E-SI               |    | <b>Wi-Fi 6 3000M Outdoor Access Point</b><br>3000 Mbps Dual-band Wi-Fi 6 Gigabit outdoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, IP68, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)                                                                                                                                                                                                                                                                      | 361             |
| DS-3WG105G-SI                |    | <b>All in One 5 Port AC Router</b><br>Concurrent Users 100, Up to 2 WAN Loadbalancing, 1 Gigabit WAN Port, 4 Gigabit PoE LAN Ports with 1 LAN/WAN Switchable, 32 APs, 58w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop/Wall                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 167             |
| DS-3WG105GP-SI               |  | <b>All in One 5 Port PoE AC Router</b><br>Concurrent Users 100, Up to 2 WAN Loadbalancing, 1 Gigabit WAN Port, 4 Gigabit PoE LAN Ports with 1 LAN/WAN Switchable, 32 APs, 58w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop/Wall                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 201             |
| DS-3WG210GP-SI               |  | <b>All in One 10 Port PoE AC Router</b><br>Concurrent Users 200, Up to 4 WAN Loadbalancing, 2 Gigabit WAN Ports with 1 WAN/LAN Switchable, 8 Gigabit PoE LAN Ports with 2 LAN/WAN Switchable, 200 APs, 75w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop                                                                                                                                                                                                                                                                                                                                                                                                                         | 304             |
| <b>Kablo (Network Cable)</b> |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                 |
| DS-1LN6UZO<br>(Solid Copper) |  | <b>Network Kabloları CAT 6</b><br>305 m CAT6 UTP Network Cable<br>Stable electrical performance, compliant with ANSI/TIA-568.2-D, IEC61156, ISO/IEC11801.<br>Compliant with RoHS 2.0.<br>• Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project.<br>• Excellent performance in the Fluke 90-meter permanent link test while working continuously at 50°C high temperature.<br>• Excellent performance in the Fluke 100-meter channel test while being continuously loaded with 57V/1A DC power (PoE).<br>• Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance. | 281             |

| ÜRÜN KODU<br>(Model Number)                    | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Liste<br>(MSRP) |
|------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <b>YENİ</b>                                    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-1LN6U-W/CCA<br/>(CCA)</b>                |    | <b>Network Kabloları CAT 6</b><br>305 m CAT6 UTP Network Cable (CCA,0.565 mm)<br>305 m cost-effective CAT6 CCA network cable<br>Full diameter and full length<br>Quality verified by Fluke test<br>Guaranteed long PoE transmission distance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>160</b>      |
| <b>DS-1LN6U-G<br/>(Solid Copper)</b>           |    | <b>Network Kabloları CAT 6</b><br>305 m CAT6 UTP Network Cable (Solid Copper, 0.55 mm, Gray)<br>Full diameter 305 m CAT6 network cable<br>Core diameter: 0.55mm<br>Excellent transmission performance using solid copper<br>Quality verified by Fluke test<br>Guaranteed long PoE transmission distance<br>Great PVC flame resistance.                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>334</b>      |
| <b>YENİ</b>                                    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-1LN6OUSPE<br/>(Solid Copper-Outdoor)</b> |    | <b>Network Kabloları CAT 6</b><br>DS-1LN6OUSPE<br>CAT6 U/UTP Outdoor Network Cable (Solid Copper, 0.55mm)<br>Stable electrical performance, compliant with ANSI/TIA-568.2-D,<br>IEC61156, ISO/IEC11801.<br>Compliant with RoHS 2.0.<br>Sheath with strong mechanical properties, and high tensile and<br>compressive strength, reducing damage during the project.<br>Excellent performance in the Fluke 90-meter permanent link test<br>while working continuously at 50°C high temperature.<br>Excellent performance in the Fluke 100-meter channel test while<br>being continuously loaded with 57 V/1 A DC power (PoE).<br>Solid-Bare Copper conductor with less resistance, and better<br>electrical properties and transmission performance.                                    | <b>376</b>      |
| <b>DS-1LN6-UU<br/>(Solid Copper-)</b>          |  | <b>Network Kabloları CAT 6</b><br>305 m CAT6 UTP Network Cable (Solid Copper, 0.565 mm, CM)<br>Full diameter 305 m CAT6 network cable<br>Core diameter: 0.565mm<br>Excellent transmission performance using solid copper<br>Quality verified by Fluke test<br>Guaranteed long PoE transmission distance<br>Great PVC flame resistance.                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>376</b>      |
| <b>Kontrol Klavyesi (Key board)</b>            |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                 |
| <b>DS-1100KI</b>                               |  | <b>Network Kontrol Klavyesi</b><br>Divide video wall into regions to manage video wall by region<br>open/close window, move window, resize window, divide window,<br>and enlarge/narrow sub-window.<br>Group and macro<br>Preview camera live image on network keyboard touchscreen<br>Quickly switch to the previous/next camera<br>Control speed dome movement via joystick<br>Play the decoder videos on video wall<br>Play the video recorder videos on network keyboard touchscreen.<br>Supports clipping and capturing during playback<br>Add devices via SDK or ONVIF protocol<br>HikCentral and KPS platforms access<br>Support up to 32 users (1 administrator and 31 operators) and<br>4,000 devices;Add/modify/delete cameras in batch<br>Import/export configuration file | <b>1862</b>     |

| ÜRÜN KODU<br>(Model Number)         | RESİM<br>(Picture)                                                                  | ÜRÜN AÇIKLAMASI / ÖZELLİK<br>(Product Description)                                                                                                                                                                                               | Liste<br>(MSRP) |
|-------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| DS-1200KI                           |    | <b>Network Kontrol Klavyesi</b><br>Full-featured network keyboard<br>Supports various cameras, NVRs, DVRs<br>Flexible 4-axis joystick<br>Buttons can be used to perform powerful functions<br>128 x 64 screen displays all important information | 627             |
| DS-1005KI                           |    | <b>USB Kontrol Klavyesi</b><br>Full-featured USB keyboard<br>Supports various cameras, NVRs, DVRs and also iVMS 4200<br>Flexible 4-axis joystick<br>Buttons can be used to perform powerful functions                                            | 399             |
| UPS                                 |                                                                                     |                                                                                                                                                                                                                                                  |                 |
| <b>YENİ</b><br>DS-UPS600(O-STD)/EU  |    | <b>600VA/360W UPS</b><br>600VA/360W,220V Backup UPS with universal port sockets and European plug<br>Socket Number 2<br>Battery Capacity 12V/7Ah<br>Battery Number 1                                                                             | 103             |
| <b>YENİ</b><br>DS-UPS1000(O-STD)/EU |   | <b>1000VA/600W UPS</b><br>1000VA/600W,220V Backup UPS with universal port sockets and European plug<br>Socket Number 2<br>Battery Capacity 12V/9Ah<br>Battery Number 1                                                                           | 129             |
| <b>YENİ</b><br>DS-UPS2000(O-STD)/EU |  | <b>2000VA/1200W UPS</b><br>2000VA/1200W,220V Backup UPS with universal port sockets and European plug<br>Socket Number 4<br>Battery Capacity 12V/9Ah<br>Battery Number 2                                                                         | 365             |
| <b>YENİ</b><br>DS-UPS3000(O-STD)/EU |  | <b>3000VA/1800W UPS</b><br>3000VA/1800W,220V Backup UPS with universal port sockets and European plug<br>Socket Number 4<br>Battery Capacity 12V/9Ah<br>Battery Number 4                                                                         | 528             |

## FİYAT LİSTESİ KULLANIM ŞARTLARI

- Bu liste fiyatı üretici tarafından önerilen fiyat listesidir.
- Ürünlerimiz 2 yıl ithalatçı firma garantisindedir.
- Vergi oranlarındaki değişiklikler fiyatlarımıza aynen yansıtılır.
- Belirtilen fiyatlara KDV oranı dahil değildir.
- Kayıt cihazlarında harddisk yoktur.Box Kameralara Lens dahil değildir.
- Fiyat listesinde belirtilen, fiyat bilgileri ,ürün kodları, ürün özellikleri, ürün açıklamaları değişiklik gösterebilir.
- Stoklar ve bulunmayan ürünlerin teslim süresi için Yetkili Distribütör firmadan bilgi alınması rica olunur.
- HIKVISION Dijital Teknoloji önceden haber vermeksizin listede yer alan fiyat koşullarını değiştirme haklarını gizli tutar.
- Oluşabilecek yazım, baskı ve dizgi hataları bağlayıcı değildir.